

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 15890 (2010): Design, Installation and Testing of Solar Timber Seasoning Kiln - Guidelines [CED 9: Timber and Timber Stores]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



भारतीय मानक
लकड़ी के लिए सौर शुष्कन भट्टी के डिज़ाइन, संस्थापन
और परीक्षण — मार्गदर्शिका

Indian Standard

DESIGN, INSTALLATION AND TESTING OF SOLAR
TIMBER SEASONING KILN — GUIDELINES

ICS 27.160; 79.020

© BIS 2010

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

FOREWORD

This Indian Standard was adopted by the Bureau of Indian Standards, after the draft finalized by the Timber and Timber Stores Sectional Committee had been approved by the Civil Engineering Division Council.

Air seasoning and kiln seasoning are the traditional methods of seasoning timber. A large number of timber seasoning kilns have been installed in the country during the last five decades or so and many more are expected to be installed in the coming years with the rapidly increasing industrialization and the growing awareness of quality control in seasoned timber for various jobs. In the early years, kiln equipments manufacturing industry has got established on the basis of research work carried out at the Forest Research Institute, Dehra Dun.

The design of a timber-seasoning kiln has a direct bearing on the quality of seasoned timber produced with regards to seasoning degrade, uniformity of moisture content and freedom from stresses after drying. The kiln to be installed have varied widely in design features, such as, constructional material, nature of air circulation, mode of heating and humidification, venting system, baffling and several other minor but important details that affect performance.

For kiln seasoning, following three different designs of timber seasoning kilns are indigenously available and are most extensively used by timber industries in India at present:

- a) Steam heated over-head internal fans reversible air circulation kilns.
- b) De-humidification kilns.
- c) Solar heated kiln.

IS 7315 : 1974 'Guidelines for design, installation and testing of timber seasoning kiln (compartment type with cross forced air circulation)' has been published for the use of timber based industries. For such kilns the mode of heating is indirect in which heating by steam, furnace flue gases or electricity is generally adopted for heating the drying air. Conventional seasoning kiln using steam heat is appropriate only to large or medium scale operations, being prohibitively expensive to install and operate for small capacities. The steam-heated kilns, however, are versatile with minimum drying defects and being uniformly efficient regardless of the prevailing weather or climatic conditions. In recent years, the escalating cost of conventional fuels like coal, oil and wood waste required for generating steam has, however, considerably increased the seasoning costs in these kilns. Need has thus been felt to design and develop a kiln using non-conventional source of energy, with minimum infrastructure as well as seasoning costs.

The composition of the Committee responsible for the formulation of this standard is given in Annex A.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*).' The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

*Indian Standard***DESIGN, INSTALLATION AND TESTING OF SOLAR
TIMBER SEASONING KILN — GUIDELINES****1 SCOPE**

This standard lays the minimum performance requirements of solar seasoning kiln for seasoning of timber and recommends essential features of equipments, design and installation to attain the desired performance. It applies only to green house type solar kilns with double glazing. Procedure for testing kiln performance has also been outlined.

**2 MINIMUM PERFORMANCE REQUIREMENTS
FOR SOLAR TIMBER SEASONING KILN**

2.1 Efficient seasoning of timber with a minimum of drying defects requires that the minimum requirements with regard to air speed past the timber surfaces in the stack, relative humidity that can be maintained and the uniformity of drying conditions within the kiln be defined. Lack of an efficient humidifying arrangement exposes the timber to increased degrade through cracking and splitting and also make case-hardening relief impossible, particularly in thick and refractory timbers. Favourable air circulation speed and distribution are essential for uniform and efficient transfer throughout the stack and for maintaining uniform drying conditions within the stack.

2.2 The kiln should be capable of attaining the operating temperature from the ambient conditions within a reasonable short period, depending upon the place of its installation and weather conditions.

2.3 The kiln should be capable of attaining up to 90 percent relative humidity within a short period (say 1 h), with the timber charge near the desired final average moisture content and already heated up.

2.4 The circulation of air should be adequate and be uniformly distributed, not less than 0.6 m/s in any layer of the timber stack. It should be reversible in direction through the stack. Air speed measurement should be done with the stacking space of the kiln fully stacked in length and height, with 25 mm thick timber and using 20 mm thick crossers.

**3 DESIGN, CONSTRUCTION AND
EQUIPMENT****3.1 Site and Layout**

The kiln should be installed at the site that provides maximum exposure to sun and should be installed

on a concrete platform measuring not less than 8.5 m × 6.0 m and raised to at least 150 mm above the surrounding ground level.

3.2 Kiln Chamber

The kiln chamber should be of wood framed super structure, consisting of wall pillars and roof studs of any hard species (for example, Sal) of 150 mm × 50 mm size placed 0.95 m apart, center-to-center. The long axis of the chamber should be created in an East-West direction. The wall pillars should be erected on a wooden foundation of size 150 mm × 100 mm, having its 100 mm side half grounded into the concrete platform. The North wall should be sheathed with 9 mm thick shuttering grade plywood and all the other walls including roof should be covered with double layer of clear transparent glass of 5 mm thick on outside and 4 mm thick inside, separated by an air gap of about 37 mm by means of wooden spacer strips.

3.3 Roof of the Kiln Chamber

The roof of the kiln should be tilted towards the south at a suitable angle by adjusting the height of the North wall but keeping the height of the South wall fixed at 2.28 m. The tilt angle should be 0.9 times the latitude of the place where the kiln is to be erected, for maximum absorption of solar radiation for use all round the year.

3.3.1 Suitable rubber beading should be used, covered with shallow channels folded from 1.15 mm galvanized iron sheet for sealing purpose.

3.4 Kiln Door

3.4.1 The kiln chamber should be provided with double paneled glass sheet, wooden framed doors of size 2.06 m wide and 1.90 m high for charging of timber.

3.4.2 The kiln chamber should be provided with at least one inspection door of size 0.56 m wide and 1.90 m high for taking out kiln samples periodically for weighing.

3.4.3 The door should be located either in the Eastern or the Western wall of the kiln chamber and should be provided with suitable heat resistant gaskets and fastening arrangements to prevent heat losses.

3.4.4 In the North wall a 1.21 m × 0.6 m plywood door should be provided for facilitating lubrication of the fan bearing and adjustment of the baffles.

3.5 Corrugated Horizontal Galvanized Iron Solar Absorber

3.5.1 The glass of the kiln naturally possesses selective transmission properties for radiation. Thus radiated solar energy transmitted through the sheathing into the kiln is absorbed by a corrugated solar panel, which heats up and emits long wave heat energy. The incoming solar radiation is trapped as heat in the kiln and the temperature rises, depending upon the prevailing weather and sky condition, the moisture content, thickness and drying rate of timber, etc.

3.5.2 Inside the kiln chamber a v-corrugated galvanized iron solar absorber measuring 5.46 m long and 2.14 m wide should be installed horizontally along the entire length of the kiln at a height of 1.90 m above floor, leaving clear gaps of 0.61 m along both the North and South walls. This absorber should be painted with dull black paint.

3.6 Air Circulation System

3.6.1 Airflow serves to carry the heat from the overhead solar absorber to the timber surfaces within the stack and to return the spent, cold and humid air for re-heating over the absorber, in addition to carrying away the evaporated water vapour from the timber surfaces.

3.6.2 Inside the kiln chamber, a vertical partition of 9 mm thick plywood from floor to false ceiling and at a distance of 0.60 m from North wall shall be provided to the entire length of kiln. The plywood partition should bear two 100 mm diameter holes, their centre being at a distance of 1.36 m.

3.6.3 Two propeller fans of reversible type, 0.9 m diameter with 12 blades should be mounted in the fan housing with their shafts supplied cross wise of the length of stack horizontally. The fans should be supported on adequate number of ball bearing on pedestal, securely fixed in order to avoid vibration.

3.6.4 Two blackened, suitably curved baffles made of galvanized iron of size not less than 1 m wide should be mounted inside the kiln running along the length of the kiln roof, from the kiln roof to North wall and from kiln roof to South wall for smoothly guiding the air circulation.

3.6.5 Two 1.30 m high and 0.90 m wide openings with removable covers shall be provided directly at the back of the two fans in the North plywood wall. To convert the re-circulating air system into a single pass forced air drying system, the covers on the

North wall openings behind the fans are removed and the 0.61 m wide North side plenum space is blocked all round these two openings by means of baffles described below, so that the fans exhaust the entire air leaving the stack through the opening in the plywood wall without it re-entering the stack, as in the re-circulating system. The baffles around each fan consist of two vertical 0.61 m high and one horizontal 1.26 m × 0.61 m framed galvanized iron sheet panels hinged to the vertical fan partitions. The two vertical panels are kept flush with the vertical fan partition and the horizontal panels flush with the false ceiling when the kiln is worked as re-circulating air system. When swung out into the North side plenum gap, the three panels block the plenum gap all round the North wall opening behind each fan and isolate the discharge of the air to the North side from the rest of the kiln, thus preventing re-circulation of the discharged air.

3.6.6 Eight vents of 300 mm × 600 mm size, four in the North wall and four in the South wall at the floor level, should be provided for fresh air intake as and when required.

3.7 Humidifier

A spinning disc humidifier capable of evaporating 37.85 litre of water/h, with a ¾ HP motor starter for 3-phase 440 V ac is installed in the North side plenum space, at the level of the solar absorbing false ceiling near the East or West end wall. A water supply connection is required to be made to the humidifier. A galvanized iron barrel attachment with a set of two strips-and-gaps type screens should be mounted on the humidifier casing to filter out and arrest coarse spray. A drain connection is required to be taken out from the barrel to remove water, that is, not converted into proper mist. The spray is worked manually by means of its starter, as and when kiln humidity needs to be raised.

NOTE — A de-humidifier unit may also be installed in the solar timber seasoning kiln in order to improve its drying efficiency.

3.8 Electric Motors

3.8.1 The kiln requires two electric motors, each of 2 HP, 14 440 rpm for 3-phase 440 V ac, complete with starters and reversing switches. In operation the actual power consumption for such fans does not exceed 1 kW, when fans of aluminium construction are used.

3.8.2 The fans inside the kiln as well as humidifier shall ordinarily be driven by electrical power. In locations where electric power is not available, a diesel engine may be used.

3.8.3 Any design of fan may be used provided that they are fully reversible and their capacity is adequate to fulfill the requirement with regards to speed laid down in **2.4**. They should preferably be made of aluminium or mild steel and painted with corrosion resistant paint.

4 CHAMBER DIMENSION, CHARGING OF KILN AND DRYING CAPACITY

4.1 The dimensions of the chamber depend upon the quality and maximum length of the timber to be seasoned and also the latitude of the place where solar kiln is to be installed. In general, the internal dimensions should be 5.5 m long and 3.35 m wide. Height of the North wall depends upon the latitude of the place.

4.2 Charging in the kiln is generally done manually.

4.3 Stacking capacity of a kiln shall be expressed in standard term as the maximum volume of 25 mm thick timber that can be stacked using 20 mm thick crossers.

4.3.1 Solar kilns of standard stacking capacity of 7.1 m³/charge are available, which can be increased by repeating the standard unit length and adding more number of fans.

5 OPERATION ROOM

The concrete platform may be walled on the North side with galvanized iron or asbestos cement sheet in order to protect the motors, reversible switch starters, etc, from rain.

6 KILN INSTRUMENTS AND LABORATORY EQUIPMENTS

6.1 For weighing the samples and checking the moisture content of wood and for determination of rate of drying kiln charge, the following instruments/equipment should be arranged.

6.1.1 Two sets of dry and wet bulb thermometers of mercury in glass type with range 20 to 100°C, one for North side and other for South side of the stack.

6.1.2 One digital weighing machine of capacity of 500 g and having an accuracy of 0.01 g.

6.1.3 One digital weighing machine to weigh up to 10 kg.

6.1.4 One electric drying oven with a digital temperature display and capable of maintaining a constant temperature of 100°C for drying small samples of wood.

6.1.5 One electrical moisture meter (useful for ready checking of the final moisture content attained).

7 KILN TESTING

7.1 A solar timber seasoning kiln may be tested for conformity to the minimum performance requirements laid down under **2.2** to **2.4** by tests described in **7.2**, **7.3** and **7.4**, which are functional in nature.

7.2 After closing the doors, vents and exhausts, fans should be started and it should be ensured that there is no leakage from anywhere. Suitable rubber beading or any other alternative arrangement shall be made to arrest leakage.

7.3 After closing the doors, vents and exhausts and after adjusting fan drive system to the prescribed rpm, the fans shall be started. The air speed between the stack layers shall be measured at different evenly distributed positions along the length and height, by inserting the probe of a suitable air speed measurement equipment (digital anemometer) up to the middle position and across the width of the stack. The air speed shall then be measured again in identical positions between the stack layers with the air circulation reversed. The result of the readings so obtained shall conform to the requirements given in **2.4**.

7.4 Humidity and temperature inside the kiln should be checked using dry and wet bulb thermometer and should conform to the requirements given in **2.2** and **2.3**. These tests should be carried out inside a fully stacked kiln.

ANNEX A

(Foreword)

COMMITTEE COMPOSITION

Timber and Timber Stores Sectional Committee, CED 9

<i>Organization</i>	<i>Representative(s)</i>
In personal capacity (2989/D, 12th Main, HAL II Stage, Bangalore 560008) Bamboo Society of India, Bangalore	SHRI SHYAM SUNDER (Chairman) SHRI A. C. LAKSHMANA DR K. A. KUSHALAPPA (<i>Alternate</i>)
Cane and Bamboo Technology Centre, Guwahati	SHRI KAMESH SALAM SHRI NIPAN DEKA (<i>Alternate</i>)
Central Building Research Institute, Roorkee Directorate General of Supplies & Disposals, New Delhi Directorate of Standardization, New Delhi Engineer-in-Chief's Branch, Army Headquarters, New Delhi	DIRECTOR DIRECTOR GENERAL DIRECTOR SHRI C. R. SAHA SHRI N. B. SHELAR (<i>Alternate</i>)
Federation of Indian Plywood & Panel Industry, New Delhi	SHRI AJAY BALDAWA SHRI B. K. BANERJEE (<i>Alternate</i>)
Forest Department, Govt. of Chhattisgarh, Raipur	SHRI R. K. SHARMA SHRI B. K. SINHA (<i>Alternate</i>)
Forest Department, Govt. of Madhya Pradesh, Bhopal	SHRI A. K. DUBEY SHRI RAVI SHRIVASTAV (<i>Alternate</i>)
Forest Research Institute, Dehra Dun	DR S. S. NEGI DR VIMAL KOTHIYAL (<i>Alternate</i>)
Indian Academy of Wood Science, Bangalore Indian Council of Forestry Research and Education, Dehra Dun	PRESIDENT DIRECTOR GENERAL
Indian Plywood Industries Research & Training Institute, Bangalore	DIRECTOR SHRI M. VENUGOPAL NAIDU (<i>Alternate</i>)
Institute of Wood Science & Technology, Bangalore	DR K. S. SHASHIDHAR DR R. V. RAO (<i>Alternate</i>)
Karnataka State Forest Industries Corporation Ltd, Bangalore	SHRI V. P. HIRAMATH SHRI S. SHIVA PRAKASH (<i>Alternate</i>)
Kerala Forest Research Institute, Peechi	DIRECTOR DR GNANAHARAN (<i>Alternate</i>)
Kutty Flush Doors & Furnitures Co Pvt Ltd, Chennai	SHRI K. SANKARA KRISHNAN COL Y. G. KRISHNAN (<i>Alternate</i>)
Mazagaon Dock Limited, Mumbai	CDS K. CHANDRA SHRI ANIL KUMAR (<i>Alternate</i>)
Ministry of Defence, Gwalior	DIRECTOR SHRI H. C. PANT (<i>Alternate</i>)
Ministry of Environment & Forests, New Delhi Naval Dockyard, Mumbai Rubber Board, Kottayam	DR BIPIN BEHARI REPRESENTATIVE SHRI M. K. BALAGOPALAN NAIR
Timber Development Association of India, Dehra Dun WIMCO Limited, Mumbai	SECRETARY DR RAMESH CHANDRA DHIMAN
In personal capacity (606 B, I Block, III Stage, UVCE Layout, WOC Road, Basaveshwaranagar Bangalore 560079, Karnataka)	SHRI K. DAMODARAN
BIS Directorate General	SHRI A. K. SAINI, Scientist 'F' and Head (CED) [Representing Director General (<i>Ex-officio</i>)]

Member Secretary
SHRIMATI MADHURIMA MADHAV
Scientist 'B' (CED), BIS

Timber Terminology, Conversion, Seasoning, Preservation,
Grading and Testing Subcommittee, CED 9:1

<i>Organization</i>	<i>Representative(s)</i>
Institute of Wood Science & Technology, Bangalore ASCU Hickson Limited, Kolkata	DR R. V. RAO (<i>Convener</i>) SHRI RAJIV AGARWAL SHRI J. BASU (<i>Alternate</i>)
Borax Morarji Limited, Coil	SHRI H. T. KAPADIA SHRI S. RANGARAJAN (<i>Alternate</i>)
Central Building Research Institute, Roorkee	DR S. P. AGARWAL SHRI B. S. RAWAT (<i>Alternate</i>)
Central Mining Research Station (CSIR), Dhanbad Controllerate of Quality Assurance, Kanpur	DIRECTOR SHRI NUSRAT ULLAH SHRI A. K. GANGULY (<i>Alternate</i>)
Directorate General of Supplies & Disposals, New Delhi Directorate of Standardization, New Delhi Forest Department, Govt. of Assam, Guwahati Forest Department, Govt. of Chhattisgarh, Raipur	DIRECTOR GENERAL DIRECTOR PRINCIPAL CHIEF CONSERVATOR OF FORESTS SHRI R. K. SHARMA SHRI B. K. SINHA (<i>Alternate</i>)
Forest Department, Govt. of Karnataka, Bangalore Forest Department, Govt. of Uttaranchal, Dehradun	PRINCIPAL CHIEF CONSERVATOR OF FORESTS PRINCIPAL CHIEF CONSERVATOR OF FORESTS GENERAL MANAGER (<i>Alternate</i>)
Forest Research Institute (Forest Products Division), Dehradun	SHRI V. K. JAIN SHRI VIMAL KOTHIAL (<i>Alternate</i>)
Forest Research Institute (Pathology Division), Dehradun	DR A. N. SHUKLA DR N. K. S. HARSH (<i>Alternate</i>)
Forest Research Institute (Systematic Botany Branch Division), Dehradun	DR S. A. S. BISWAS DR SMER CHAND (<i>Alternate</i>)
Forest Research Institute (Wood Anatomy Division), Dehradun	DR (SHRIMATI) SANGITA GUPTA DR P. K. PANDEY (<i>Alternate</i>)
Forest Research Institute (Wood Preservation Division), Dehradun	DR (SHRIMATI) SADHANA TRIPATHI SHRI AZMAL SAMANI (<i>Alternate</i>)
Forest Research Institute (Wood Seasoning Division), Dehradun	SHRI NIRMAL UPRETI DR KISHAN KUMAR (<i>Alternate</i>)
Gurdit Institute Pvt Limited, Dharwar Himachal Pradesh State Forest Corporation Ltd, Shimla	SHRI YASH KARAN SINGH MANAGING DIRECTOR EXECUTIVE DIRECTOR (<i>Alternate</i>)
Indian Council of Forestry Research and Education, Dehradun	SHRI B. K. BHATIA SHRI S. K. KOHLI (<i>Alternate</i>)
Indian Plywood Industries Research & Training Institute, Bangalore	SHRI K. C. MATHEWS SHRI ANAND NANDANWAR (<i>Alternate</i>)
Indian Rubber Wood Task Force, Kottayam	SHRI C. BHASKAR NAYAR SHRI V. J. MATHEW (<i>Alternate</i>)
Institute of Wood Science & Technology (Wood Properties & Uses Division), Bangalore Karnataka State Forest Industries Corporation Ltd, Bangalore	DR S. R. SHUKLA SHRI V. P. HIRAMATH SHRI S. SHIVA PRAKASH (<i>Alternate</i>)
Kerala Forest Research Institute, Peechi	DIRECTOR DR K. M. BHATT (<i>Alternate</i>)
Kutty Flush Doors & Furnitures Co Pvt Ltd, Chennai	SHRI K. SANKARA KRISHNAN COL Y. G. KRISHNAN (<i>Alternate</i>)
Madhya Pradesh Rajya Van Vikas Nigam Ltd, Bhopal Ministry of Environment & Forests, New Delhi North-East Institute of Science and Technology, Jorhat Office of Development Commissioner (Handicrafts), New Delhi	SHRI A. K. DUBEY DR BIPIN BEHARI DIRECTOR DEPUTY DIRECTOR
Rubber Research Institute of India, Kottayam Western India Plywoods Ltd, Kannur	DIRECTOR SHRI P. K. MAYAN MOHAMED DR K. RAGHUNATHAN (<i>Alternate</i>)
In personal capacity (<i>C/o American Connexion, 214, Phase II Vasant Vihar, Dehradun 248006, Uttaranchal</i>)	DR SATISH KUMAR

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards : Monthly Additions'.

This Indian Standard has been developed from Doc No.: CED 9 (7357).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 2323 0131, 2323 3375, 2323 9402

Website: www.bis.org.in

Regional Offices:

	Telephones
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{ 2323 7617 2323 3841
Eastern : 1/14 C. I. T. Scheme VI M, V. I. P. Road, Kankurgachi KOLKATA 700054	{ 2337 8499, 2337 8561 2337 8626, 2337 9120
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022	{ 260 3843 260 9285
Southern : C. I. T. Campus, IV Cross Road, CHENNAI 600113	{ 2254 1216, 2254 1442 2254 2519, 2254 2315
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400093	{ 2832 9295, 2832 7858 2832 7891, 2832 7892

Branches: AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. DEHRADUN. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. NAGPUR. PARWANOO. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM. VISAKHAPATNAM.