

BLANK PAGE



IS 8008 (Part 5): 2003

भारतीय मानक पेयजल पूर्ति के लिए अन्तःक्षेपण संचकित एच डी पी ई फिटिंगें—विशिष्टि

भाग 5 फेरूल रिड्यूसरों की विशिष्ट अपेक्षाएँ

(पहला पुनरीक्षण)

Indian Standard

INJECTION MOULDED/MACHINED HIGH DENSITY POLYETHYLENE (HDPE) FITTINGS FOR POTABLE WATER SUPPLIES—SPECIFICATION

PART 5 SPECIFIC REQUIREMENTS FOR FERRULE REDUCERS

(First Revision)

ICS 83.140.30;91.140.60

© BIS 2003

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

FOREWORD

This Indian Standard (Part 5) (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Plastic Piping System Sectional Committee had been approved by the Civil Engineering Division Council.

This standard covers general requirements for injection moulded/machined HDPE fittings which are used for connection by welding process to HDPE pipes covered by IS 4984:1995 'High density polyethylene pipe for water supply (fourth revision)'.

This standard was first published in 1976. Keeping in view the developments in this field and considering revision of IS 4984 this standard has been revised.

The requirements of injection moulded/machined HDPE fittings are covered in nine parts. The other parts in this series are:

(Part 1): 2003 General requirements for fittings

(Part 2): 2003 Specific requirements for 90° bends

(Part 3): 2003 Specific requirements for 90° tees

(Part 4): 2003 Specific requirements for reducers

(Part 6): 2003 Specific requirements for pipe ends

(Part 7): 2003 Specific requirements for sandwich flanges

(Part 8): 2003 Specific requirements for reducing tees

(Part 9): 2003 Specific requirements for end caps

All revised parts have been aligned with IS 4984 with respect to grade of material, dimensional requirements, testing procedures and sampling methodology.

Provisions has been made for rewelding, in case any weld gets rejected. Weld length had been kept constant with a uniform tolerance.

Drawings have been revised from short neck pipe ends to long neck pipe ends. The range of diameter of fittings, weld length and clarity of the dimensions in the drawings had been incorporated in each part of the standard, wherever applicable.

This standard covers general requirements for materials, manufacture, dimensions, tolerances, etc, for ferrule reducer. Specific requirement of different types of fittings are covered in separate parts of this standard.

Fittings from 20 mm to 315 mm are manufactured by the injection moulding methods and machined, wherever so required and fittings of 355 mm and above shall be manufactured by machining process from thick walled extruded pipes or compression moulded slabs.

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2:1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

INJECTION MOULDED/MACHINED HIGH DENSITY POLYETHYLENE (HDPE) FITTINGS FOR POTABLE WATER SUPPLIES—SPECIFICATION

PART 5 SPECIFIC REQUIREMENTS FOR FERRULE REDUCERS

(First Revision)

1 SCOPE

This standard (Part 5) covers the specific requirements for material, manufacture, dimensions, tolerances and marking for injection moulded and machined HDPE ferrule reducers for potable water supplies.

2 REFERENCE

The following standard contains provisions which, through reference in this text, constitutes provisions of this standard. At the time of publication the edition indicated was valid. All standards are subject to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below:

IS No.

Title

8008 (Part 1): 2003

Injection moulded/machined high density polyethylene (HDPE) fittings for potable water supplies— Specification: Part 1 General requirements for fittings

3 REQUIREMENTS

3.1 General

The general requirements for material, manufacture, grade, sizes, performance requirements, methods of test sampling and inspection shall conform to IS 8008 (Part 1).

3.2 Manufacture

3.2.1 A typical illustration of injection moulded ferrule

reducer is shown in Fig. 1.

3.2.2 Laying Length

The overall laying length (Z) and tolerances thereon shall comply with those given in Table 1 read with Fig. 1.

3.2.3 The outside diameters and wall thickness of fitting at ends shall comply with requirements given in 8 of IS 8008 (Part 1).

4 MARKING

- 4.1 Each ferrule reducer fitting shall be clearly marked at a prominent place, with the following information:
 - a) Identification of source of manufacture, and
 - b) The size of the fittings, grade of material and appropriate class (working pressure) to which the pressure rating of the fitting corresponds.

4.2 BIS Certification Marking

Each reducer fitting may also be marked with the Standard Mark.

4.2.1 The use of the Standard Mark is governed by the provisions of the *Bureau of Indian Standards Act*, 1986 and the Rules and Regulations made thereunder. The details of conditions under which a licence for the use of the Standard Mark may be granted to the manufacturers or the producers may be obtained from the Bureau of Indian Standards.




Fig. 1 Ferrule Reducer

Table 1 Dimension for Ferrule Reducers

(Clause 3.2.2)

All dimensions in millimetres.

SI No.	$D_{_1}$	D ₂	$L_{_1}$	L ₂	Z
(1)	(2)	(3)	(4)	(5)	(6)
i)	32	63	18	18	48.0
ii)	90	63	24	18	74.3
iii)	110	63	30	18	89.4
iv)	150	63	42	18	98.5
v)	225	63	57	18	102.8
vi)	250	63	62	18	108.5
vii)	280	63	72	18	122.4
viii)	315	63	82	18	134.2
ix)	355	63	94	18	145.2
x)	400	63	108	18	155.3
xi)	450	63	120	18	162.4
xii)	500	63	132	18	170.8
xiii)	550	63	144	18	188.1
xiv)	630	63	162	18	204.4

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

Amend No.

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publication), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc: No. CED 50 (5922).

Amendments Issued Since Publication

Date of Issue

	BUREAU OF INDIAN STANDARDS	
Headquart	ers:	
	avan, 9 Bahadur Shah Zafar Marg, New Delhi 110002 ss: 2323 0131, 2323 3375, 2323 9402	Telegrams: Manaksanstha (Common to all offices)
Regional (Offices:	Telephone
Central	: Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{2323 7617 2323 3841
Eastern	: 1/14 C.I.T. Scheme VII M, V.I.P. Road, Kankurgachi KOLKATA 700054	{2337 8499, 2337 8561 2337 8626, 2337 9120
Northern	: SCO 335-336, Sector 34-A, CHANDIGARH 160022	$\begin{cases} 60\ 3843 \\ 60\ 9285 \end{cases}$
Southern	: C.I.T. Campus, IV Cross Road, CHENNAI 600113	{2254 1216, 2254 1442 2254 2519, 2254 2315
Western	: Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400093	
Branches	: AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. CC GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPU	

NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM. VISAKHAPATNAM.

Text Affected